




teas. Rolitea Rollers have been modernised by T & I incorporating such changes as would increase operational convenience and life of the machine. Rolitea – the modern Orthodox Tea Roller, now in use in all orthodox tea producing areas in India and abroad.



FEATURES

- · Graded and seasoned castings
- Table of superior quality Stainless Steel
- Heavy duty original bearings (of renowned make)
- Cranks, Gears and other vital components made of special quality steel for safety

WORM REDUCER DRIVE

Rolitea is driven not through the traditional Bevel Gear but a special vertical Worm Reducer of 30:1 ratio, coupled directly to a 1500 rpm motor, giving the table speed of 50 RPM. The arrangement is such that an intermediate V-drive can be incorporated to get a different speed.

This improved drive arrangement offers these positive advantages:

- Eliminates large and inconvenient V-Pulleys and Belts
- Makes the machine more compact thus saving precious space
- Enables the use of standard and more economical motors
- · Cuts on maintenance and down time
- · Ensures desired table speed
- · Reduces unpleasant, harsh noise




ROLITEA LEAF JACKET (HOOD)

Made of high quality stainless steel sheet. Its adequate thickness reduces wear and tear. The top and bottom edges of the jacket are re-enforced for extra strength.

The two-tone painting of Rolitea gives it a smooth, perfect finish.

PRESSURE CAP

Electrically operated
Pressure Cap has been
introduced on Rolitea for
the first time. It is
automatic, free-floating
and fitted with height
indicator. Thus it
eliminates complex,
mechanical system making
operation simpler and
smoother.



Electronic Pressure Cap controller specially developed for the Rolltea is available as an optional. The entire rolling cycle is pre-programmed as desired, thus minimising labour and improving quality.

TABLE DESIGN




Rolitea Rolling Table is furnished with improved high-efficiency Asymmetric Well with a sliding Door. Rolitea with Battens, Cones and Drop Doors are also available. The highly polished table surface ensures best results.

TECHNICAL DATA

Code	Туре	Size mm (inch)	Approx. Leaf capacity (kgs)	Recommended Motor H.P. (KW)	Approx floor space mm
DA 090	Double Action	900 (36)	125 — 150	10/15 (7.5/11)	2000 x 2100
SA 090	Single Action	900 (36)	125 — 150	10/15 (7.5/11)	2000 x 2100
DA 115	Double Action	1150 (46)	300 — 350	15/20 (11/15)	2700 x 2210
SA 115	Single Action	1150 (46)	300 — 350	15/20 (11/15)	2700 x 2210

Excludes 1 HP motor for electric operated Pressure Cap.









Corporate Office

19. R. N. Muknesse Road. Rostoro 700 001. West Bengal, NDA Phone : 91 33 2948 2223, Fax : 91 33 2210 0788 ermai : sakss@real.bkt

stigui Office

"Agree House" VT-9/8 STAC Road. Mologus Trigus 734 403 (West Bengal) Phone: 91 363 251 4605 Fax: 91 353 251 2190. Email: eliqui-liteat.bb

Tinsukia Office

Malum Rood, Udyog Nogal, Breuko 786 146, Asiam Phone : (91 374; 233 9773/2036, Fax : (91 374; 233 0086 emol: trisulto(a)to(a)to

Sezpur Office

Teopus 784 001, Assam Prone : 91 3712 25 50045 Fax: 91 3712 25 5007 ornal : texput@leol.bit